

*Challenger*

# Mid-Range Tractors

110–150 HP









## SERIES:

### MT400E

You can't control the weather, but with the right Challenger® mid-range tractor, you sure can control your productivity. Powerful, reliable and easy to operate, these tractors quickly shift from brush-cut mowing, roadside trimming and snow blowing to leveling, clearing and highway construction. No matter what your needs are, you get the stability and versatility to handle tougher jobs, so you know your tractor won't let you down.

## SEGMENTS:

-  Ag tech schools & universities
-  Brush-cut mowing  
(Power lines, tall grass)
-  Land reclamation  
(Highway construction, establish new grass, feed sources for wildlife)
-  Roadside mowing & trimming  
(Batwing, shoulder & boom mower  
5'-7' mower - small areas  
7'-10' mower - large areas)
-  Park trail maintenance  
(Leveling & clearing)
-  Snow removal & grooming

## MT400E Series

You demand performance. You need versatility. The MT400E Series delivers both and then some. From the side of the road to the end of the trail, this is the machine that will remind you why you don't want a desk job. When the job has to get done, and the job changes every day, the versatility and dependability of the MT400E Series will make you glad it's part of your crew.



## MID-RANGE TRACTORS

Series	MT400E				
Model	MT455E	MT465E	MT475E	MT485E	MT495E
Rated Engine HP	110 @ 2,100 RPM 4 CYL	115 @ 2,100 RPM 4 CYL	130 @ 2,100 RPM 4 CYL	140 @ 2,100 RPM 4 CYL	150 @ 2,100 RPM 4 CYL
PTO HP	90 540/540E or 540/540E/1000/1000E	95 540/540E or 540/540E/1000/1000E	105 540/540E/1000/1000E	115 540/540E or 540/540E/1000/1000E	125 540/540E or 540/540E/1000/1000E
Transmission	16F/16R AutoPower IV	16F/16R AutoPower IV	TechStar CVT	16F/16R AutoPower IV or 24F/24R AutoPower VI or TechStar CVT	24F/24R AutoPower VI or TechStar CVT
2WD/4WD	4WD	4WD	4WD	4WD	4WD
Hydraulics GPM (LPM)	15 (57) or 26 (100) or 29 (110)	15 (57) or 26 (100) or 29 (110)	29 (110) or 50 (190)	15 (57) or 26 (100) or 29 (110) or 50 (190)	15 (57) or 26 (100) or 29 (110) or 50 (190)
3-point Hitch Lift Cap @ 24" Behind Pin lbs. (kg.)	Cat 2/3 8,520 (3,872)	Cat 2/3 8,520 (3,872)	Cat 2/3 11,400 (5,182)	Cat 2/3 AutoPower IV/VI 8,520 (3,872) TechStar CVT 11,400 (5,182)	Cat 2/3 AutoPower VI 8,520 (3,872) TechStar CVT 11,400 (5,182)
Weight ROPS/CAB lbs. (kg.)	15,432 (7,000)	15,432 (7,000)	15,432 (7,000)	15,432 (7,000)	15,432 (7,000)
Loader	ML51/ML61 ML56/ML58/ML68	ML51/ML61 ML56/ML58/ML68	ML51/ML61 ML56/ML58/ML68	ML51/ML61 ML56/ML58/ML68	ML51/ML61 ML56/ML58/ML68
Backhoe					
Disc Mower					
Finishing Mower					
Snow Removal	✓	✓	✓	✓	✓
Rear Blades	✓	✓	✓	✓	✓
Box Scrapers	✓	✓	✓	✓	✓
Grading Scrapers	✓	✓	✓	✓	✓
Landscape Rakes					
Power Rakes					
Core Aerators					
Pulverizers	✓	✓	✓	✓	✓
Stump Grinders	✓	✓	✓	✓	✓
Post Hole Diggers	✓	✓	✓	✓	✓
Chippers & Shredders					
Rotary Tillers (Fwd & Rev)					
Rotary Tillers (Fwd)					
Seeder					
Batwing Mower	✓	✓	✓	✓	✓
Rotary Cutter					

AGCO Government Sales: 800-972-2426 | [challenger-ag.us](http://challenger-ag.us)

©2016 AGCO Corporation. Challenger is a brand of AGCO. AGCO is a registered trademarks of AGCO Corporation. Challenger is a trademark of Caterpillar, Inc. and is used under license by AGCO. All rights reserved. AG16PO17CR.

AGCO may at any time, and from time to time, for technical or other necessary reasons, modify any of the data, specifications or warranty of the products described herein. Some equipment shown may be optional.

